

TM 15

Lighweight aluminium safety tripod

CEN/TS 16415, EN 795/



The lightweight TM15 aluminium safety tripod is an anchor point according to EN795/B and TS16415/B and can be used as a fall protection equipment.

The TM15 tripod provides protection for up to 3 people at a time. The TM15 tripod consists of a powder-coated aluminium head with 3 ball-bearing polyamide rollers. The tripod is also equipped with 3 anchorage points on the side walls of the tripod head. Each of these points can be used as an anchor point for equipment to protect against falls from height. One point is designed for a maximum of one user at a time



**VIDEO
PRODUCT PRESENTATION**
<https://vimeo.com/651618945>

SPECIAL FEATURES



**ZABEZPIECZENIE
DLA 3 OSÓB**

PARAMETERS

Height	313 cm
Mounting hole diameter Ø	174 mm
Leg spacing	149 mm
Weight of tripod	28.7 kg
Tripod weight with transport packaging	30 kg
Transport dimensions	226 x 33 x 29 mm
Max. number of users for lifting and lowering	3
Max. weight of load to be lifted or lowered	1000 kg

NOGI

Material	aluminium
Finishing	anodizing

Length	400 cm
--------	--------

GŁOWICA

Material	aluminium alloy
Finishing	powdercoat
Number of anchorage points	3
Rollers	yes
Number of rolls	3

STOPKI

Material	galvanized steel
----------	------------------

ŁAŃCUCH

Material	galvanized steel
----------	------------------

VARIANTS

cat.

AT017

ADDITIONAL PHOTOS





PHOTOS 360 (ROTATING)



