



**FA 60 023 20**



**FA 60 023 20R**

①





**Fourni avec**  
**Provided with**  
**Suministrado con**  
**Fornito con**  
**Geliefert mit**



**FA 60 101 02P**



<b>HS CODE</b>
84251900
<b>CARTON SIZE / PCS.</b>
43.5 x 27.5 x 27.5 cm / 1
<b>Certificate of Test</b> n°SPC0268347/1810 Issue 3 Extension 1
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom

REF.	FA 60 023 20	FA 60 023 20R
LG.	20 m	20 m
CE	EN 1496:2017 Class B	
	x1	
	135 KG	
MAT. 	STEEL Ø 6.0 mm	ARAMID Ø 6.5 mm
R (kN) / MBS (kN)	---	---
+	(1) EN 13157 (1) Machinery Directive: 250 KG (1) Secondary brake mechanism / Independent reel mode (2) Compatible FA 60 001 00, FA 60 002 00 (2) Compatible FA 60 101 00, FA 60 102 00, in combination with FA 60 101 01A (2) Compatible FA 60 022 00, in combination with FA 60 022 06A	
	11.36 KG	10.39kg



**Nombre d'utilisateurs**  
Number of users  
**Cantidad de usuarios**  
Quantità di utilizzatori  
**Anzahl der Benutzer**



**Charge maxi admissible**  
Max. allowed load  
**Carga máxima admisible**  
Carico massimale ammissibile  
**Zulässige Höchstlast**



**Matière câble**  
Material wire rope  
**Material cable**  
Material dei cavo  
**Material Seil**

+

**R (kN) / MBS**

(1)  
**Point fort**  
Key feature  
**Ventaja principal**  
Punti forti  
**Produktvorteil**

(2)  
**À utiliser avec**  
To be used with  
**Para usar con**  
Ad essere utilizzato con  
**Verwendet werden soll mit**

**Résistance statique (en kN) / Résistance à la rupture (en kN)**  
Static strength (kN) / Minimum Breaking Strength (kN)  
**Resistencia estática (en kN) / Resistencia a la ruptura (kN)**  
Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**