

GasAlert Quattro

Multi-Gas (1-4) Detector

H₂S, CO, O₂, LEL



Visual auditing, easy compliance

Rugged and reliable, the GasAlertQuattro four-gas detector combines a comprehensive range of features with simple one-button operation. With flexible power options, the GasAlertQuattro is always ready. The graphic LCD displays easy to identify icons that indicate operational information, such as bump test and calibration status for simplified onsite auditing. IntelliFlash™ provides continuous visual confirmation of detector operation and compliance. Suited to a wide range of industrial applications including confined space entry, the GasAlertQuattro is fully compatible with BW's MicroDock II automatic test and calibration system.

Meets ACGIH 1 ppm H₂S TWA recommendations.




Visit www.honeywellanalytics.com to download the latest Fleet Manager II update.

Standard Package Contents:

- GasAlertQuattro detector
- Rechargeable battery pack or alkaline pack with three AA batteries
- Charger wall plug (with rechargeable battery option)
- Calibration cap and hose
- Reversible screwdriver
- Manual



General Specifications

Size	5.1 x 3.2 x 1.9 in. / 13.0 x 8.1 x 4.7 cm	
Weight	- 11.15 oz. / 316 g (with rechargeable battery pack) - 11.92 oz. / 338 g (with alkaline battery pack)	
Typical battery life	AA alkaline:	14 hours (+68 to 122°F / +20 to 50°C)
	Rechargeable:	20 hours (+68 to 122°F / +20 to 50°C) 18 hours (-4 to +32°F / -20 to 0°C)
Certifications and approvals		Class I, Div. 1, Gr. A, B, C, D
	ATEX:	II 1 G Ga Ex ia IIC T4
	IECEX:	Ex ia IIC T4
		Marine Equipment Directive (MED) 96/98/EC
		American Bureau of Shipping
	CE:	European Conformity
	EU Ex :	CU TR Ex (Customs Union)
	IP Rating:	IP 66/67
ATEX performance approval	EN 60079-29-1, EN 50104, EN 45544-1/-2, EN 50271	
Warranty	Full three-year warranty including all sensors	

Gas Legend

%LEL	Combustible (W)
O ₂	Oxygen (X)
H ₂ S	Hydrogen sulfide (H)
CO	Carbon monoxide (M)